

# H.J. Bennett Ltd.

## Declaration of Performance

Certificate number: DOP 004U

1. Unique identification code for product:	0/4mm Grit
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	0/4mm G <sub>F</sub> 85 G <sub>Tc</sub> 25
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Aggregates for Unbound & Hydraulically Bound Materials for use in Civil Engineering Work and Road Construction.
4. Name, registered trade name or registered trade mark and contact address as required under Article 11(5):	H.J.Bennett Ltd. Seafield Garage, Faulkner Lane, Sandown, Isle of Wight. PO36 8HH. Tel: 01983 873415 Fax 01983 407488 Email: info@hjbennett.co.uk
5. Not needed.	n/a
6. System or systems of assessment and verification of consistency of performance of the construction product as set out in CPR, Annex V:	System 4
7. In case of the declaration of performance concerning a construction product covered by the harmonized standards.	BS EN 13242:2013 Aggregates for Unbound & Hydraulically Bound Materials for use in Civil Engineering Work and Road Construction.

### 8. Essential Characteristics

Essential Characteristics:	Performance:	Harmonized Technical Specification:
<b>Particle size</b> d/D	0/4mm	<b>BS EN 13242</b>
Category	G <sub>F</sub> 85	
<b>Cleanliness</b> fines content F	f <sub>3</sub>	
<b>Particle shape</b>	NPD	
<b>Particle density</b>	NPD	
<b>Loose bulk density</b>	NPD	
<b>% Crushed particles</b>	NPD	
<b>Water absorption / suction</b>	NPD	

Essential Characteristics:	Performance:	Harmonized Technical Specification:
<b>Resistance to fragmentation/ crushing</b> <b>Resistance to abrasion</b> <b>Durability against freeze / thaw</b> <b>Release of dangerous substances.</b> <b>Volume stability</b> <b>Composition / Content</b> Total sulphur S Acid soluble sulphates AS Classification of coarse recycled aggregates. Water soluble sulphates of recycled aggregates. Constituents which alter the rate of setting and hardening of hydraulically bound mixtures. Resistance to attrition Release of heavy metals by leaching.	NPD NPD NPD NPD NPD  NPD NPD NPD NPD  NPD NPD NPD NPD NPD NPD NPD	<b>BS EN 13242</b>

9. The performance of the production identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Authorized by:

Date:

Name: Nigel Bennett

Position: Managing Director

Certificate number: DOP 004U